


Ornamental notching provides architectural appearance for exposed applications.


**Materials:** See chart  
**Finish:** USP primer

**Installation:**  
 • Use all specified fasteners. See Product Notes, page 11.




**KHL33-O**

Some model designs may vary from illustration shown



**T**



**L**

©Copyright 2011 USP Structural Connectors®

| USP Stock No. | Ref. No. | Steel Gauge | Description | Dimensions |        |        | Bolt Schedule <sup>1</sup> |      | Code Ref. |
|---------------|----------|-------------|-------------|------------|--------|--------|----------------------------|------|-----------|
|               |          |             |             | W          | H      | L      | Qty                        | Dia. |           |
| KHL33-O       | OHA33    | 7           | Heavy Angle | 3-1/4      | ---    | 2-1/2  | 2                          | 5/8  | 120       |
| KHL36-O       | OHA36    | 7           | Heavy Angle | 3-1/4      | ---    | 6      | 4                          | 5/8  |           |
| KHST64-O      | OHS135   | 7           | Strap Tie   | 6          | ---    | 13-1/2 | 4                          | 3/4  |           |
| ST12-O        | OS       | 12          | Strap Tie   | 2          | ---    | 12     | 4                          | 1/2  |           |
| L12-O         | OL       | 12          | 'L' Strap   | 2-1/2      | 11-7/8 | 11-7/8 | 5                          | 1/2  |           |
| LH12-O        | OHL      | 7           | 'L' Strap   | 2-1/2      | 11-7/8 | 11-7/8 | 5                          | 5/8  |           |
| T1212-O       | OT       | 12          | 'T' Strap   | 2-1/2      | 11-7/8 | 14-1/2 | 6                          | 1/2  |           |
| TH12-O        | OHT      | 7           | 'T' Strap   | 2-1/2      | 11-7/8 | 11-1/8 | 4                          | 5/8  |           |
| TH16-O        | ---      | 7           | 'T' Strap   | 2-1/2      | 11-7/8 | 16-1/8 | 6                          | 5/8  |           |

1) All bolts shall meet or exceed the specifications of ASTM A 307.