

**SW** – Light-duty hanger.

**SWH** – Medium-duty hanger.

**KHW** – Heavy-duty hanger installs with NA20D nails for higher load capacities.

**Materials:** SW top flange - 12 gauge;  
stirrup - 12 gauge;  
SWH top flange - 7 gauge;  
stirrup - 12 gauge;  
KHW top flange - 3 gauge;  
stirrup - 10 gauge.

**Finish:** USP primer

**Options:** All nominal lumber sizes are available for rough/full size lumber. See Specialty Options below.

**Codes:** ESR-2104, FL820,  
L.A. City RR 25745

**Installation:**

- Use all specified fasteners. See Product Notes, page 11.
- NA20D nails are supplied with KHW hangers.
- For welded installations see page 198.
- **KHW models are not recommended for use with LVL, PSL, or LSL members.**

**Nailer Installation Chart** – chart represents maximum allowable loads for hangers used on wood nailers. Reference page 115.

USP Stock No.	Nailer Size	Fastener Schedule <sup>1,2,3</sup>		Allowable Loads (Lbs.) <sup>4</sup>	
		Header	Joist	DF-L / SP	S-P-F
SW	2X	(2) 10d x 1-1/2	(2) 10d x 1-1/2	1635	1115
SWH	2X	(2) 10d x 1-1/2	(2) 10d	2600	1770
	3X	(2) 16d x 2-1/2	(2) 10d	3350	2280
KHW	3X	(4) 16d x 2-1/2	(2) 10d	5180	3525

- 1) 10d x 1-1/2 nails are 9 gauge (0.148" diameter) by 1-1/2" long.
- 2) 16d x 2-1/2 nails are 8 gauge (0.162" diameter) by 2-1/2" long.
- 3) Minimum nail embedment shall be 1-1/2" for 10d nails.
- 4) Listed loads shall not be increased.

**Specialty Options Chart** – refer to Specialty Options pages 194, 196 to 197 for additional details.

Option	Skewed <sup>1</sup>	Sloped Seat <sup>2</sup>	Sloped / Skewed <sup>1,2</sup>	Sloped Top Flange <sup>3</sup>	Top Flange Offset		Saddle	Ridge
Range	1° to 84°	1° to 45°	See Sloped Seat and Skewed	0° to 35°	-- --		-- --	0° to 45°
Allowable Loads	100% of table load	100% of table load	100% of table load	Reduce allowable table loads using straight-line interpolation	Hanger Width 3-1/2" or less 3-9/16" to 5-1/2" 5-9/16" to 7-1/2"	% of table load: 60% 75% 85%	100% of table load per side	100% of table load
Ordering	Add SK, angle required, and right (R) or left (L), to product number. Ex. SW212-SK45R	Add SL, slope required, and up (U) or down (D), to product number. Ex. SW212-SL30D	See Sloped Seat and Skewed. Ex. SW212-SK45RSL30D	Add SF, angle required, and right (R) or left (L), to product number. Ex. SW212-SF30L	Add OS, and right (R) or left (L), to product number. Ex. SW212-OSL		Add SA, and saddle width required to product number. Ex. SW212-SA=5-1/2"	Add DA, angle required to product number. Ex. SW212-DA30

- 1) Skewed hangers with skews greater than 15° may have all joist nailing on outside flange.
- 2) Sloped or sloped / skewed hangers with slopes greater than 15° may have additional joist nails.
- 3) Sloped top flanges with greater than 15° may have additional header nails.

## LIGHT GAUGE PURLIN HANGERS – HL SERIES

These top mount hangers are designed for supporting floor joists or 2x purlins. The top mount style allows builders to drop in joists or purlins quickly.


**Materials:** 18 gauge

**Finish:** G90 galvanizing


**Codes:** ESR-1280, FL11664, LA City RR 25749

**Installation:**


- Use all specified fasteners. See Product Notes, page 11.




Typical **SW210** installation




**SW210**




Typical **KHW46** installation



**KHW46**



**SWH410**



**HL210**

Hangers

Beam/ Joist Size	USP Stock No.	Ref. No.	Steel Gauge	Dimensions						Fastener Schedule <sup>3,4</sup>					Allowable Loads (Lbs.) <sup>5</sup>				Code Ref.
				W	H	D	L	TF	Header		Joist			DF-L / SP					
									Qty		Type	Qty	Type	Floor	Roof	Uplift <sup>1,2</sup>			
									Top	Face							100%	115%	
2 x 4	HDO24	HU24TF	12	1-9/16	3-7/16	2-1/4	---	2-1/2	4	2	16d	2	10d x 1-1/2	2170	2170	2170	315	5, F30, R5	
	HL26	JB26, LB26	18	1-9/16	5-3/8	1-1/2	---	1-5/16	2	4	16d	2	prongs	1270	1270	1270	---	2, F20, R12	
2 x 6	SW26	W26	12	1-9/16	5-3/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO26	HU26TF	12	1-9/16	5-3/8	2-1/4	---	2-1/2	4	6	16d	4	10d x 1-1/2	2590	2615	2615	770	5, F30, R5	
2 x 8	HL28	JB28, LB28	18	1-9/16	7-5/16	1-3/4	---	1-5/16	2	4	16d	2	prongs	1590	1590	1590	---	2, F20, R12	
	SW28	W28	12	1-9/16	7-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO28	HU28TF	12	1-9/16	7-1/8	2-1/4	---	2-1/2	4	6	16d	4	10d x 1-1/2	2590	2660	2710	755	5, F30, R5	
2 x 10	HL210	JB210, LB210	18	1-9/16	9-5/16	2	---	1-5/16	2	4	16d	2	prongs	1590	1590	1590	---	2, F20, R12	
	SW210	W210	12	1-9/16	9-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO210	HU210TF	12	1-9/16	9-1/8	2-1/4	---	2-1/2	4	8	16d	4	10d x 1-1/2	2590	2660	2710	725	5, F30, R5	
2 x 12	HL212	JB212, LB212	18	1-9/16	11-1/4	2-1/8	---	1-5/16	2	4	16d	2	prongs	1590	1590	1590	---	2, F20, R12	
	SW212	W212	12	1-9/16	11-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO212	HU212TF	12	1-9/16	11	2-1/4	---	2-1/2	4	10	16d	6	10d x 1-1/2	2355	2355	2355	1150	5, F30, R5	
2 x 14	HL214	JB214, LB214	18	1-9/16	13-1/8	2	---	2-1/2	2	6	16d	2	10d x 1-1/2	1590	1590	1590	360	2, F20, R12	
	SW214	W214	12	1-9/16	13-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO214	HU214TF	12	1-9/16	13	2-1/4	---	2-1/2	4	12	16d	6	10d x 1-1/2	2830	2935	3010	1050	5, F30, R5	
2 x 16	SW216	W216	12	1-9/16	15-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO216	HU216TF, LB216	12	1-9/16	15	2-1/4	---	2-1/2	4	14	16d	8	10d x 1-1/2	3070	3215	3310	1535	5, F30, R5	
3 x 4	HDO34	HU34TF	12	2-9/16	3-7/16	2-1/2	---	2-1/2	4	4	16d	2	10d x 1-1/2	2665	2665	2665	315	5, F30, R5	
3 x 6	SW36	W36	12	2-9/16	5-3/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO36	HU36TF	12	2-9/16	5-3/8	2-1/2	---	2-1/2	4	6	16d	4	10d x 1-1/2	3010	3010	3010	770	5, F30, R5	
3 x 8	SW38	W38	12	2-9/16	7-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO38	B38, HU38TF	12	2-9/16	7-1/8	2-1/2	---	2-1/2	4	8	16d	4	10d x 1-1/2	3605	3605	3605	755	5, F30, R5	
3 x 10	SW310	W310	12	2-9/16	9-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d x 1-1/2	2315	2315	2315	---	8, F14, R9	
	HDO310	B310, HU310TF	12	2-9/16	9-1/8	2-1/2	---	2-1/2	4	10	16d	6	10d x 1-1/2	4165	4165	4165	1150	5, F30, R5	
3 x 12	SWH312	WNP312	7/12	2-9/16	11-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d x 1-1/2	3305	3305	3305	---	8, F14, R9	
	HDO312	B312, HU312TF	12	2-9/16	11	2-1/2	---	2-1/2	4	12	16d	6	10d x 1-1/2	4475	4475	4475	1150	5, F30, R5	
3 x 14	SWH314	WNP314	7/12	2-9/16	13-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d x 1-1/2	3305	3305	3305	---	8, F14, R9	
	HDO314	B314, HU314TF	12	2-9/16	13	2-1/2	---	2-1/2	4	14	16d	8	10d x 1-1/2	4475	4475	4475	1315	5, F30, R5	
3 x 16	SWH316	WNP316	7/12	2-9/16	15-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d x 1-1/2	3305	3305	3305	---	8, F14, R9	
	HDO316	B316, HU316TF	12	2-9/16	15	2-1/2	---	2-1/2	4	16	16d	8	10d x 1-1/2	4865	5010	5105	1535	5, F30, R5	
(2) 2 x 4	HDO24-2	HU24-2TF	12	3-1/8	3-7/16	2-1/4	---	2-1/2	4	4	16d	2	10d	2445	2445	2445	405	5, F30, R5	
(2) 2 x 6	SWH26-2	WNP26-2	7/12	3-1/8	5-3/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9	
	HDO26-2	HU26-2TF, HUS26-2TF	12	3-1/8	5-3/8	2-1/4	---	2-1/2	4	6	16d	4	10d	3050	3050	3050	815	5, F30, R5	
(2) 2 x 8	SWH28-2	WNP28-2	7/12	3-1/8	7-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9	
	HDO28-2	HU28-2TF, HUS28-2TF	12	3-1/8	7-1/8	2-1/4	---	2-1/2	4	8	16d	4	10d	3825	3825	3825	815	5, F30, R5	
(2) 2 x 10	SWH210-2	WNP210-2	7/12	3-1/8	9-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9	
	HDO210-2	HU210-2TF, HUS210-2TF	12	3-1/8	9-1/8	2-1/2	---	2-1/2	4	10	16d	6	10d	4565	4565	4565	1220	5, F30, R5	

1) Uplift Loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.  
2) HL, KHW, SW, and SWH products do not provide uplift resistance, except for the HL214.  
3) Minimum nail embedment shall be 1-1/2" for 10d nails, 1-5/8" for 16d nails, and 2" for NA20D nails.  
4) 10d x 1-1/2 nails are 9 gauge (0.148" diameter) by 1-1/2" long.  
5) NA20D nails are 6 gauge (0.192" diameter) by 2-1/2" long and are included with KB, KHB, and KHW hangers.  
6) KHW Glulam load values are based on 560 psi perpendicular to grain loading.

# TOP MOUNT HANGER CHARTS CONTINUED



©Copyright 2011 USP Structural Connectors®

Beam/ Joist Size	USP Stock No.	Ref. No.	Steel Gauge	Dimensions					Fastener Schedule <sup>3,4,5</sup>				Allowable Loads (Lbs.) <sup>6</sup>				Code Ref.	
				W	H	D	L	TF	Header		Joist		DF-L / SP					
									Qty	Type	Qty	Type	Floor	Roof	Uplift <sup>1,2</sup>			
				100%	115%	125%	160%											
(2) 2 x 12	SWH212-2	WNP212-2	7/12	3-1/8	11-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	HDO212-2	HU212-2TF, HUS212-2TF	12	3-1/8	11	2-1/2	---	2-1/2	4	12	16d	6	10d	4880	5230	5465	1220	5, F30, R5
(2) 2 x 14	SWH214-2	WNP214-2	7/12	3-1/8	13-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	HDO214-2	HU214-2TF, HUS214-2TF	12	3-1/8	13	2-1/2	---	2-1/2	4	14	16d	8	10d	5175	5410	5410	1625	5, F30, R5
(2) 2 x 16	SWH216-2	WNP216-2	7/12	3-1/8	15-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	HDO216-2	HU216-2TF	12	3-1/8	15	2-1/2	---	2-1/2	4	16	16d	8	10d	5475	5855	5960	1625	5, F30, R5
4 x 4	HDO44	HU44TF	12	3-9/16	3-7/16	2-1/4	---	2-1/2	4	4	16d	2	10d	2445	2445	2445	405	5, F30, R5
4 x 6	SW46	W46	12	3-9/16	5-3/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d	2520	2520	2520	---	8, F14, R9
	HDO46	HU46TF, HUS46TF	12	3-9/16	5-3/8	2-1/4	---	2-1/2	4	6	16d	4	10d	3050	3050	3050	815	5, F30, R5
	KHW46	HW46	3/10	3-9/16	5-3/8	2-1/2	10	2-1/2	4	---	NA20D	2	10d	5335	5335	5335	---	8, F14, R9
4 x 8	SW48	W48	12	3-9/16	7-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d	2520	2520	2520	---	8, F14, R9
	HDO48	B48, BA48, HU48TF, HUS48TF	12	3-9/16	7-1/8	2-1/4	---	2-1/2	4	8	16d	4	10d	3825	3825	3825	815	5, F30, R5
	KHW48	HW48	3/10	3-9/16	7-1/8	2-1/2	10	2-1/2	4	---	NA20D	2	10d	5335	5335	5335	---	8, F14, R9
4 x 10	SW410	W410	12	3-9/16	9-1/8	2-1/2	6-1/2	2-1/2	2	---	10d	2	10d	2520	2520	2520	---	8, F14, R9
	HDO410	B410, HU410TF, HUS410TF	12	3-9/16	9-1/8	2-1/4	---	2-1/2	4	10	16d	6	10d	4565	4565	4565	1220	5, F30, R5
	SWH410	---	7/12	3-9/16	9-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	KHW410	HW410	3/10	3-9/16	9-1/8	2-1/2	10	2-1/2	4	---	NA20D	2	10d	5335	5335	5335	---	8, F14, R9
4 x 12	HDO412	B412, HU412TF, HUS412TF	12	3-9/16	11	2-1/4	---	2-1/2	4	12	16d	6	10d	4880	5230	5465	1220	5, F30, R5
	SWH412	WNP412	7/12	3-9/16	11-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	KHW412	HW412	3/10	3-9/16	11-1/8	2-1/2	10	2-1/2	4	---	NA20D	2	10d	5335	5335	5335	---	8, F14, R9
4 x 14	HDO414	B414, HHB414, HU414TF, HUI414TF, HUS414TF	12	3-9/16	13	2-1/2	---	2-1/2	4	14	16d	8	10d	5175	5410	5410	1625	5, F30, R5
	SWH414	WNP414	7/12	3-9/16	13-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	KHW414	HW414	3/10	3-9/16	13-1/8	2-1/2	10	2-1/2	4	---	NA20D	2	10d	5335	5335	5335	---	8, F14, R9
4 x 16	HDO416	B416, HHB416, HU416TF	12	3-9/16	15	2-1/2	---	2-1/2	4	16	16d	8	10d	5475	5915	6210	1625	5, F30, R5
	SWH416	WNP416	7/12	3-9/16	15-1/8	2-1/2	7	2-1/2	2	---	10d	2	10d	3305	3305	3305	---	8, F14, R9
	KHW416	HW416	3/10	3-9/16	15-1/8	2-1/2	10	2-1/2	4	---	NA20D	2	10d	5335	5335	5335	---	8, F14, R9
(3) 2 x 10	HDO210-3	HU210-3TF	12	4-11/16	9-1/8	2-1/2	---	2-1/2	4	10	16d	6	16d	4565	4565	4565	1430	5, F30, R5
(3) 2 x 12	HDO212-3	HU212-3TF	12	4-11/16	11	2-1/2	---	2-1/2	4	12	16d	6	16d	4880	5230	5465	1430	5, F30, R5

- 1) Uplift Loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.
- 2) HL, KHW, SW, and SWH products do not provide uplift resistance, except for the HL214.
- 3) Minimum nail embedment shall be 1-1/2" for 10d nails, 1-5/8" for 16d nails, and 2" for NA20D nails.
- 4) 10d x 1-1/2 nails are 9 gauge (0.148" diameter) by 1-1/2" long.
- 5) NA20D nails are 6 gauge (0.192" diameter) by 2-1/2" long and are included with KB, KHB, and KHW hangers.
- 6) KHW Glulam load values are based on 560 psi perpendicular to grain loading.

continued on next page